

IN THE SPECIFICATION

(AS ORIGINALLY FILED)

On page 9, paragraph 1, please delete the originally filed paragraph 1 and replace paragraph 1 with the amended paragraph 1 as follows:

Sub
D

As described above, with reference to Figures 3 and 4, the front 305 of the chassis 302 suitably includes the slots 303 for receiving the PCB modules 312. In the present exemplary embodiment, the front 305 of the chassis 302 preferably includes an upper horizontal beam 308 and a lower horizontal beam 336 configured with slots to receive a plurality of vertical beams 310. The upper and lower horizontal beams 308 and 336 are suitably configured with positioning pins 356 and 360 to initially position the vertical beams 310 within the slots formed in the upper and lower horizontal beams 308 and 336. The vertical beams 310 are then bolted through bolt holes 354 and 358 formed in the vertical beams 310 and upper and lower horizontal beams 308 and 336. With particular reference to Figure 4, the upper horizontal beam 308 is suitably attached to the top panel 304 with bolts 410. Similarly, the lower horizontal beam 336 is suitably attached to the bottom panel 340. It should be recognized, however, that the slots 303 for receiving the PCB modules 312 can be formed using any convenient method. For example, rather than using the horizontal and vertical beams 308, 336 and 310, the front 305 can be formed as a single piece.